



DIMENSIONAL SPECIFICATIONS

Schedule or S.D.R.	Normal Pipe Size Inches	Outside Diameter Inches	Maximum Working Pressure PSI at 73°	Minimum Wall Thickness Inches	Average Inside Diameter Inches	Weight of Pipe per Ft. (lbs.)
SCHD 40	1/2	.840	600	.109	.602	.164
SCHD 80			850	.147	.526	.206
SDR 13.5			315	.062	.616	.106
SCHD 40	3/4	1.050	480	.113	.804	.218
SCHD 80			690	.154	.722	.278
SDR 21			200	.060	.870	.131
SCHD 40	1	1.315	450	.133	1.029	.321
SCHD 80			630	.179	.936	.409
SDR 21			200	.063	1.135	.174
SCHD 40	1 1/4	1.660	370	.140	1.380	.434
SCHD 80			520	.191	1.255	.567
SDR 21			200	.080	1.480	.268
SDR 26			160	.064	1.522	.225
SCHD 40			330	.145	1.590	.518
SCHD 80	1 1/2	1.900	470	.200	1.476	.686
SDR 21			200	.090	1.700	.345
SDR 26			160	.073	1.720	.289
SCHD 40			280	.154	2.047	.695
SCHD 80	2	2.375	400	.218	1.913	.949
SDR 21			200	.113	2.129	.530
SDR 26			160	.091	2.173	.440
SCHD 40			300	.203	2.445	1.096
SCHD 80	2 1/2	2.875	420	.276	2.290	1.449
SDR 21			200	.137	2.581	.768
SDR 26			160	.110	2.635	.663
SDR 32.5			125	.088	2.689	.521
SCHD 40			260	.216	3.042	1.435
SCHD 80	3	3.500	370	.300	2.864	1.938
SDR 21			200	.167	3.146	1.127
SDR 26			160	.135	3.210	.932
SDR 32.5			125	.108	3.264	.764
SDR 41			100	.085	3.310	.620



DIMENSIONAL SPECIFICATIONS

Schedule or S.D.R.	Normal Pipe Size Inches	Outside Diameter Inches	Maximum Working Pressure PSI at 73°	Minimum Wall Thickness Inches	Average Inside Diameter Inches	Weight of Pipe per Ft. (lbs.)
SCHD 40	4	4.500	220	.237	3.998	2.043
SCHD 80			320	.337	3.786	2.833
SDR 21			200	.214	4.046	1.858
SDR 26			160	.173	4.133	1.521
SDR 32.5			125	.138	4.204	1.234
SDR 41			100	.110	4.260	1.007
SCHD 40	5	5.563	190	.258	5.016	2.776
SCHD 80			290	.375	4.768	3.938
SDR 21			200	.265	5.001	2.830
SDR 26			160	.214	5.107	2.320
SDR 32.5			125	.171	5.199	1.876
SDR 41			100	.136	5.271	1.515
SCHD 40	6	6.625	180	.280	6.031	3.600
SCHD 80			280	.432	5.709	5.411
SDR 21			200	.316	5.955	4.010
SDR 26			160	.255	6.084	3.295
SDR 32.5			125	.204	6.193	2.652
SDR 41			100	.162	6.281	2.126
SDR 64		63	.104	6.417	1.380	
SCHD 40	8	8.625	160	.322	7.941	5.427
SCHD 80			250	.500	7.565	8.219
SDR 21			200	.410	7.756	6.790
SDR 26			160	.332	7.921	5.550
SDR 32.5			125	.265	8.063	4.491
SDR 41			100	.210	8.180	3.589
SDR 64		63	.135	8.355	2.320	
SCHD 40	10	10.750	140	.365	9.976	7.683
SCHD 80			230	.593	9.493	12.195
SDR 21			200	.511	9.667	10.540
SDR 26			160	.413	9.874	8.600
SDR 32.5			125	.331	10.048	6.992
SDR 41			100	.262	10.195	5.584



DIMENSIONAL SPECIFICATIONS

Schedule or S.D.R.	Normal Pipe Size Inches	Outside Diameter Inches	Maximum Working Pressure PSI at 73°	Minimum Wall Thickness Inches	Average Inside Diameter Inches	Weight of Pipe per Ft. (lbs.)
SCHD 40	12	12.750	130	.406	11.888	10.171
SCHD 80			230	.687	11.294	16.765
SDR 21			200	.606	11.465	14.760
SDR 26			160	.490	11.711	12.110
SDR 32.5			125	.392	11.919	9.829
SDR 41			100	.311	12.091	7.850
SCHD 40	14	14.000	130	.438	13.072	12.400
SCHD 40	16	16.000	130	.500	14.936	15.916
SCHD 40	18	18.000	130	.562	16.809	20.110